

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Claims 1–22: (Cancelled)

Claim 23. (Previously Presented) An apparatus for generating route guidance information based on route information supplied from outside, comprising:

a storage unit configured to store road network data and landmark data;

a road pattern analysis unit configured to analyze a road pattern along a route of the route information by referring to the road network data, and to obtain road pattern data;

a landmark selection unit configured to select landmark data based on the road pattern data and the road network data from said storage unit;

a route guidance information generation unit configured to generate the route guidance information using the road pattern data and the landmark data selected by said landmark selection unit; and

a presentation unit configured to present the route guidance information.

24. (Previously Presented) The apparatus according to claim 23,
wherein the road network data includes a plurality of nodes and a plurality
of arcs each connecting two nodes;

wherein node data of each node includes a node identifier, a node
position, a node name, the number of arcs connecting the node, and an arrangement of
arc identifiers connecting the node; and

wherein arc data of each arc includes an arc identifier, positions of a
starting point and an end point of the arc, an arc name, and an arc width.

25. (Previously Presented) The apparatus according to claim 23, wherein
the landmark data includes a landmark identifier, a landmark name, a class of the
landmark, a priority degree, and a position of the landmark.

26. (Previously Presented) The apparatus according to claim 23, wherein
said road pattern analysis unit measures an angle difference between two roads each
connected to a junction on the route.

27. (Previously Presented) The apparatus according to claim 23, wherein
said landmark selection unit selects the landmark data based on geometrical
information of the route and the road pattern data.

28. (Previously Presented) The apparatus according to claim 23, wherein said landmark selection unit selects the landmark data included in an area of which center position is a junction on the route, a size of the area being calculated based on a width of each road connected to the junction.

29. (Previously Presented) The apparatus according to claim 28, wherein said landmark selection unit divides the area into a plurality of landmark selection areas by each road connected to the junction, assigns a priority degree, based on an advance direction along the route, to each of the plurality of landmark selection areas, and selects at least one landmark included in the landmark selection area based on the priority degree of each landmark selection area, the priority degree of each landmark, and a distance from the route to each landmark.

30. (Previously Presented) The apparatus according to claim 26, wherein said storage unit includes a decision dictionary configured to store a plurality of expressions of route guidance in correspondence with the angle difference between two roads and a pattern of the junction, the expression of route guidance representing for a user how to advance the junction.

31–32. (Canceled)

33. (Previously Presented) A method for generating route guidance information based on route information supplied from the outside, comprising:

- storing road network data and landmark data in a memory;
- analyzing a road pattern along a route of the route information by referring to the road network data;
- selecting landmark data based on the road pattern and the road network data from the memory;
- generating the route guidance information using the road pattern and the selected landmark data; and
- presenting the route guidance information.

34. (Previously Presented) The method according to claim 33,

- wherein the road network data includes a plurality of nodes and a plurality of arcs each connecting two nodes;
- wherein node data of each node includes a node identifier, a node position, a node name, the number of arcs connecting the node, and an arrangement of arc identifiers connecting the node; and
- wherein arc data of each arc includes an arc identifier, positions of a starting point and an end point of the arc, an arc name, and an arc width.

35. (Previously Presented) The method according to claim 33, wherein the landmark data includes a landmark identifier, a landmark name, a class of the landmark, a priority degree, and a position of the landmark.

36. (Previously Presented) The method according to claim 33, wherein the analyzing further comprises measuring an angle difference between two roads each connected to a junction on the route.

37. (Previously Presented) The method according to claim 33, wherein the selecting further comprises selecting the landmark data based on geometrical information of the route and the road pattern.

38. (Previously Presented) The method according to claim 33, wherein the selecting further comprises selecting the landmark data included in an area of which center position is a junction on the route, a size of the area being calculated based on a width of each road connected to the junction.

39. (Previously Presented) The method according to claim 38, further comprising:

dividing the area into a plurality of landmark selection areas by each road connected to the junction;

assigning a priority degree to each of the plurality of landmark selection areas based on an advance direction along the route; and

selecting at least one landmark included in the landmark selection area based on the priority degree of each landmark selection area, the priority degree of each landmark, and a distance from the route to each landmark.

40. (Previously Presented) The method according to claim 36, further including storing in a decision dictionary of the memory a plurality of expressions of route guidance in correspondence with the angle difference between two roads and a pattern of the junction, the expression of route guidance representing for a user how to advance the junction.

41–42. (Canceled)